

| ECU pin-outs | | | |
|---------------------|-------------------------------|---------------------|--------------------|
| | 2-relay engine | if different | Test values |
| 1 | Temperature sensor I (air) | | See chart |
| 2 | Full load switch | | |
| 3 | Injector 1 | | |
| 4 | Injector 2 | | |
| 5 | Injector 3 | | |
| 6 | Injector 4 | | |
| 7 | Pressure sensor | | 90 ohms to pin 15 |
| 8 | Pressure sensor | | 350 ohms to pin 10 |
| 9 | Throttle switch | | |
| 10 | Pressure sensor | | |
| 11 | Earth | | |
| 12 | Trigger points | | |
| 13 | Temperature sensor I (air) | | See chart |
| 14 | Throttle switch | | |
| 15 | Pressure sensor | | |
| 16 | Fuel pump relay | | |
| 17 | Throttle switch | | |
| 18 | Starter relay | Starter solenoid | |
| | Thermal time switch | Thermal time switch | |
| | Cold start injector | Cold start injector | |
| 19 | Fuel pump relay | | |
| 20 | Throttle switch | | |
| 21 | Trigger points | | |
| 22 | Trigger points | | |
| 23 | Temperature sender II (water) | | See chart |
| 24 | Power supply relay | | |
| 25 | Not used | | |
| Temperature senders | | | |
| | Temp. (deg. C) | 1 - air | 2 - water |
| | degrees C | Ohms | Ohms |
| | -10 | 960 | 9,200 |
| | 0 | 640 | 5,900 |
| | 10 | 435 | 3,700 |
| | 20 | 300 | 2,500 |
| | 30 | 210 | 1,700 |
| | 40 | 150 | 1,180 |
| | 50 | 110 | 840 |
| | 60 | 80 | 600 |
| | 70 | 80 | 435 |
| | 80 | 80 | 325 |
| | 90 | 80 | 250 |
| | 100 | 80 | 190 |